

■ Sliding support T h=111 50 x 5 mm 168 mm EPDM hot-dip galv.



Commercial details

| | |
|---------------|---------------|
| Part no. | 145fb0168 |
| EAN/GTIN | 4250928460219 |
| Packing unit | 1 pcs |
| Quantity unit | pcs |
| Weight | 8,14 kg/pc |
| Product group | 14-148 |
| Price unit | 1 |

QR code



Certification



Specification

| | |
|---------------|-----------|
| Specification | T-support |
| Closure screw | M12 |

Technical data

| | |
|-------------------------|--------------------|
| Material | Steel |
| Material type | S235 |
| Surface | hot-dip galvanized |
| Insulation thickness | 6 mm |
| Temperature resistance | -35 °C - 100 °C |
| Sound insulation lining | Rubber EPDM |
| Safety factor | 1,54 |
| Class | B2 |

Product details

| | |
|-------------------------------|---------|
| Outer pipe diameter | 168 mm |
| Material dimension pipe clamp | 50x5 mm |
| Width substructure | 100 mm |
| Height base | 111 mm |
| Length of substructure | 250 mm |
| load Fx | 3,42 kN |
| load Fy | 3 kN |
| load Fz hanging μ 0,2 | 6,4 kN |
| load Fz hanging μ 0,3 | 6,4 kN |
| load Fz standing μ 0,2 | 12,8 kN |
| load Fz standing μ 0,3 | 10 kN |